DERWENT-ACC-NO: 2002-691673

DERWENT-WEEK:

200337

COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE:

Multilayer chirped mirror for

causing preset

negative/positive group delay time

has multiple

individual layers contiguous via

parallel, planar

boundary layers and applied to

support substrate

INVENTOR: KRAUSZ, F; TEMPEA, G F

PATENT-ASSIGNEE: FEMTOLASERS PRODN GMBH[FEMTN]

PRIORITY-DATA: 2001AT-0000302 (February 26, 2001)

PATENT-FAMILY:

PUB-NO

PUB-DATE

LANGUAGE

MAIN-IPC PAGES

AT 410721 B

May 15, 2003

N/A

000

G02B 005/08

WO 200268999 A2

September 6, 2002

020

G02B 005/00

AT 200100302 A

November 15, 2002

N/A

000

G02B 005/08

. DESIGNATED-STATES: AE AG AL AM AU AZ BA BB BG BR BY BZ CA

CH CN CO CR CU DM DZ

EC ES GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC

LK LR LS LT LU LV

MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO RU SD SE SG SI

SL TJ TM TN TR TT

TZ UA UG US UZ VN YU ZA ZM ZW AT BE CH CY DE DK EA ES FI FR

GB GH GM GR IE IT

KE LS LU MC MW MZ NL OA PT SD SE SL SZ TR TZ UG ZM ZW

APPLICATION-DATA:

PUB-NO

APPL-DESCRIPTOR

APPL-NO

APPL-DATE

AT 410721B

N/A

2001AT-0000302 Fe AT 410721B Pre

February 26, 2001

Previous Publ. AT 200100302

N/A

ری کی سے

WO 200268999A2 N/A

2002WO-AT00057 February 21, 2002

AT 200100302A N/A

2001AT-0000302 February 26, 2001

INT-CL (IPC): G02B005/00, G02B005/08, H01S003/08

ABSTRACTED-PUB-NO: WO 200268999A

## BASIC-ABSTRACT:

NOVELTY - Multiple individual layers (2,3) applied to a support substrate (4) are contiguous via parallel, planar boundary layers and have different optical constants and different thicknesses. A wedge-shaped front glass platelet (5) fastens on an outer individual layer (2) facing away from the support substrate by means of optical bonding.

DETAILED DESCRIPTION - An INDEPENDENT CLAIM is also included for a method for producing a multilayer chirped mirror.

USE - In laser devices.

ADVANTAGE - It is possible to have the mirror's impedance ideally adapted to an external medium. Surface quality, e.g. in a range of lambda /6- lambda /10, can be suitable for laser applications.

DESCRIPTION OF DRAWING(S) - The drawing shows a structural diagram of a multilayer chirped mirror with a wedge-shaped front glass platelet.

Multiple individual layers 2,3

Support substrate 4

Wedge-shaped front glass platelet 5

Outer individual layer 2

CHOSEN-DRAWING: Dwg.1/5

TITLE-TERMS: MULTILAYER CHIRP MIRROR CAUSE PRESET NEGATIVE

POSITIVE GROUP DELAY

TIME MULTIPLE INDIVIDUAL LAYER CONTIGUOUS

PARALLEL PLANE BOUNDARY

LAYER APPLY SUPPORT SUBSTRATE

DERWENT-CLASS: P81 U12 V07 V08

EPI-CODES: U12-A01B; V07-F02A; V08-A01A; V08-A04A;

V08-A04C;

SECONDARY-ACC-NO:

Non-CPI Secondary Accession Numbers: N2002-545644